

SSCOR S-SCORT III



Rugged & Reliable Portable Suction

The S-SCORT® III is the leader in today's EMS environment! It provides all of the power and versatility necessary to quickly and effectively clear an airway, weighs only 7 pounds and is economical to purchase and maintain.

The S-SCORT III is housed in a light weight, rigid foam core package designed to meet the physical demands of the most active EMS service.

It is simple, rugged, powerful, quick and easy to use AND is very economical both in the short and long term; low cost to purchase and inexpensive to maintain.



Model # 74000

Complete information at www.sscor.com

Built for today's first Responders Designed for Ease of use Engineered to last

S-SCORT® III

The S-SCORT III delivers >30 LPM clinical airflow and vacuum is regulated by a two position regulator, allowing the operator to choose between full power (>525mmHg) and reduced power (120mmHg +/- 15%) for endotracheal and pediatric suction procedures.

Features:

- Lightweight, durable portable suction device
- Vinyl coated nylon over foam construction
- Inexpensive to purchase and maintain
- Powered by a rechargeable sealed lead acid battery
- >30 LPM clinical airflow
- Two position regulator providing a vacuum selection of >525mmHg or 120mmHg +/- 15%
- 1 year warranty



Specifications:

Performance:	>30 lpm clinical airflow, > 525 mmHg vacuum
Dimensions:	8"H x 7"W x 11"L (20.3cmH x 17.8cmW x 27.9cmL)
Weight:	7 lbs. (3.18 Kgs.)
Power Source:	Internal Battery or DC power cord connected to vehicle
Battery Run Time:	30-45 minutes when fully charged
Charger:	115V AC to 12V DC dual mode charger
Chassis:	Durable closed cell foam and vinyl wipe down fabric
Regulator:	Two position



Standard items included with product:

Dual Mode Charger, DC Power Cord, canister, 2m patient tube, S-SCORT SDC Catheter™ (Formerly the S-SCORT DuCanto Catheter), and Quickstart Guide.

S-SCORT

2125 N. Madera Rd. Unit C, Simi Valley, CA 93065 USA

+ 1 818-504-4054

www.sscor.com Email sales@sscor.com shop.sscor.com

LIT 74000 Rev E